
REV 08.11.23
Article 1208
Unit name

LBK-AT2000Bu



		Supply
Air flow	[m^3/h]	2000
Static pressure	[Pa]	200
Temperature SUMMER	[°C]	28
Relative humidity SUMMER	[%]	60
Temperature WINTER	[°C]	-7
Relative humidity, WINTER	[%]	90
Unit SFP	[$W/(m^3/s)$]	1809.6

Heating type		Water
Temperature, Heater outlet	[°C]	20
Required power	[kW]	18.6
Water temperature IN	[°C]	80
Water temperature OUT	[°C]	60
Glycol	[%]	25
Max heating capacity	[kW]	47.9

Heater

Galvanized steel case equipped with air and drain valves.

Copper pipe manifold.

Heat exchange surface made of aluminium plates.

Outlet header is equipped with a spigot for installation of an immersion temperature sensor or freezing protection mechanism.

Temperature, Heater inlet	[°C]	-7	Max heating capacity	[kW]	47.9
Temperature, Heater outlet	[°C]	20	Water pressure	[kPa]	6.7
Relative humidity, Heater inlet	[%]	90	Water flow	[l/s]	0.24
Relative humidity, Heater outlet	[%]	13	Water temperature IN	[°C]	80
Required power	[kW]	18.6	Water temperature OUT	[°C]	60
Air pressure drop	[Pa]	17.5	Glycol	[%]	25
Face air velocity	[m/s]	1.4			

Fans, winter

FAN TYPE 1

Fan, winter		
Number of fans		1
RPM	[1/min]	2368.6
Electric power consumption, Pe	[W]	1005.3
Current, I	[A]	1.6
Total fan pressure , Pf	[Pa]	925.7
Phase/voltage	[50/60Hz/VAC]	~3, 380/480
Static fan pressure , Psf	[Pa]	911.5
Static fan efficiency η es	[%]	50.4
Airflow at operating point	[m^3/h]	2000
Power rated	[W]	1100
Current rated	[A]	1.7
Control voltage	[V]	9.8
Sound pressure level to environment @3m with A filter	[dB(A)]	48.5

SFP, winter		
SFP	[$W/(m^3/s)$]	1809.6

Acoustic data

Parameters		**Octave frequency bands [Hz]**								**Gen.**
Frequency		63	125	250	500	1000	2000	4000	8000	[dB(A)]
Lw, to inlet	[dB]	73	72	81	76	69	68	60	55	77
Lw, to outlet	[dB]	80	78	84	82	79	77	70	66	84
Lw, to environment	[dB]	67	61	77	54	44	39	37	30	69
Lpa (to inlet), 3 m	[dB(A)]									56
Lpa (to outlet), 3 m	[dB(A)]									63
Lpa (to environment), 3 m	[dB(A)]									48

Filter


Parameters		
Type		panel
Make		TECHNOGAJA
Filter class		ePM1 70%/F7/MERV13
Energy Efficiency Class		E
Filter Size (WxHxD)	[mm]	1x403x403x48

Parameters		
Face velocity	[m/s]	1.39
Initial Pressure Drop	[Pa]	644
Final Pressure Drop	[Pa]	744
Design Pressure Drop	[Pa]	694
Filter Media		Synthetic fiber PES

Casing


Double skin frameless casing with 40 mm mineral wool 90 kg/m3; non-flammable; outer skin: zinc-aluminum; inner skin: zinc-aluminum; EN1886 class: D1, T3, TB4.

L	W	H	H1	S1	H2
2000	1000	630	500	800	170



Controls

Control system features functions activated based on the devices installed on the air handling unit:
Coils management: electric heater, water cooler, direct expansion, cooler/heater coil;
Fans management: 3 speed setup, air pressure control, airflow control;
Temperature and/or humidity control;
Automatic summer/winter (cooling/heating) changeover;
Operation in comfort, precomfort or economy mode;
Selection of up to four daily time bands, with settings for each operating mode;
Holiday and special day function, with reduced set point;
Air quality control with optional CO2/IAQ probe;
Priority to temperature or humidity control, by room/supply/extract sensors
Protection: antifreeze, overheating, dirty filters, fire, etc.
Parameter settings divided by level, user, installer or manufacturer, with password-protected access;
Manual functioning mode;
Supervisor protocol: Modbus slave build-in, Bacnet build-in;
Freecooling and freeheating;
Pumps management, overload alarms and anti-blocking for each pump;
WEB-interface via integrated Ethernet port



ERP		
Trade mark		AT
Model		LBK-AT2000Bu
Declared typology		NRVU UVU
Type of drive installed		Integrated MSD
Type of heat recovery system		None
Thermal efficiency of heat recovery	[%]	0
Supply flow rate	[m^3/s]	0.56
Effective electric power input	[W]	1005.3
SFPint	[$W/(m^3/s)$]	2755.6
Face velocity at design flow rate	[m/s]	1.4
External pressure	[Pa]	200
Internal pressure drop of ventilation components	[Pa]	694
Static efficiency of fans	[%]	50.4
Maximum leakage rates	[%]	2.7
Maximum leakage rates	[%]	2.7
Performance of filters		B
Visual filter warning		Visual filter warning
Sound power level	[db]	69
Internet address		www,air-transfer.nl

Accessories

SKU	Title	Quantity
A29	A29 control panel (controller A31)	1

Extended Control panel provides access to engineering menu, alarm logs. service settings, unit configuration. Access to engineering manu protected by password.Used only with A31 controller.




AV03 roof	Roof for outdoor installation	1

Belimo R3020-4-B1+LR24A-SR	Three-way motorized ball valve	1

Three-way valves are designed to regulate water flows in the piping circuits of heating / cooling heat exchangers.

Dimensions [mm]	
Belimo	H1
R3020+LR24A-SR	180

Technical data	
Three-way valve with electric actuator	Belimo R3020 Belimo LR24A-SR
Connection/diameter	Tread/DN20
Max capacity [m3/h]	2.3
Pipe diameter	3/4"



DTV 500	Filter pressure switch	1

The pressure differential switch is used to determine air rarefaction or air (non-aggressive gases) pressure drop. It is used in ventilation systems to determine air filter clogging degree or belt breaking in centrifugal fans, etc.



RN 800x500	External grill	1

Outdoor grill made of extruded aluminum profile, internal louvers and protective grid IP20 made of galvanized steel. Grill is powdercoated in white.
Dimensions, LXH [mm] 800x500

VVG 800x500	Flexible duct connection	1

Flexible connectors are flanges interconnected by antvibration material. The inserts are made of galvanized steel and polyethylene tape reinforced with polyamide textile cloth

Dimensions [mm]

Size	L	H
VVG 800x500	800	500

